

VIMASCO CORP -- VINYL MASTIC WEATHER BARRIER, WC-7 -- 8040-00N037845

=====
MSDS Safety Information
=====

FSC: 8040
MSDS Date: 01/10/1992
MSDS Num: BQVDZ
LIIN: 00N037845
Tech Review: 12/15/1992
Product ID: VINYL MASTIC WEATHER BARRIER, WC-7
Responsible Party
Cage: 14947
Name: VIMASCO CORP
Box: 516
City: NITRO WV 25143 US
Info Phone Number: 304-755-3328
Emergency Phone Number: 304-755-3328
Review Ind: N

=====
Contractor Summary
=====

Cage: 14947
Name: VIMASCO CORP
Box: 516
City: NITRO WV 25143 US
Phone: 304-755-3328

=====
Ingredients
=====

Cas: 94-51-9
RTECS #: UB8787500
Name: 1-PROPANOL, 3,3'-OXYDI, DIBENZOATE; (DIPROPYLENE GLYCOL DIBENZOATE)
(MFR CAS # 20109-39-1). VP: 2.29 X 10⁻⁷ MMHG 77F.
% by Wt: 5
Ozone Depleting Chemical: N

=====
Health Hazards Data
=====

LD50 LC50 Mixture: LD50 (ORAL,RAT): 2,500 MG/KG.
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: MILD IRRITATION TO EYES, SKIN, AND NASAL.

Explanation Of Carcinogenicity: NOT RELEVANT.

Signs And Symptions Of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated By Exposure: NONE KNOWN.

First Aid: SKIN: WASH WITH SOAP AND WATER. EYE: FLUSH WITH CLEAN WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, CONSULT PHYSICIAN.

INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF IRRITATION PERSISTS, CONSULT PHYSICIAN. INGESTION: GIVE TWO GLASSES OF WATER, INDUCE VOMITING, CONSULT PHYS OR POISON CONTROL CENTER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
Handling and Disposal
=====

Spill Release Procedures: MAJOR SPILLS SHOULD BE COLLECTED FOR DISPOSAL. MINOR SPILLS MAY BE FLUSHED TO SEWER IF REGULATIONS PERMIT. BEFORE DRYING, PRODUCT MAY BE WASHED AWAY WITH WATER; AFTER DRYING, REMOVE WITH A PAINT SCRAP ER OR STRONG SOLVENT.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS. REVIEW HAZARD SECTION OF MSDS BEFORE ATTEMPTING CLEANUP. EMPTY CONTAINERS ARE NON HAZARDOUS UNDER RCRA AS INDUSTRIAL WASTE.

Handling And Storage Precautions: KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION. STORE INDOORS AT TEMPERATURES OF 45-90F.

Other Precautions: AVOID BREATHING VAPORS AND APPLICATION TO HOT SURFACES, AS VAPORS MAY BE IRRITATING. FOR INDUSTRY/PROFESSIONAL USE ONLY. NOT INTENDED FOR RETAIL SALE OR USE BY INDIVIDUAL CONSUMERS. DO NOT REUSE CONTAINER FOR POTABLES OR EDIBLES.

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: TCC

Flash Point Text: 212F,100C

Extinguishing Media: FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT (FP N).

Unusual Fire/Explosion Hazard: PRODUCT WILL NOT BURN UNTIL AFTER IT HAS BOILED OR EVAPORATED.

=====
Control Measures
=====

Respiratory Protection: IN RESTRICTED VENT AREA, USE NIOSH/MSHA APPROVED CHEM VAPOR RESPIRATOR. IN APPLICATIONS WHERE MISTS OR SPRAY MAY BE GENERATED, AVOID INHAL OF AIRBORNE PARTICULATES BY USING AN APPROVED RESP W/ORGANIC VAP CARTRIDGE W/PREFILTER FOR MIST/DUST.

Ventilation: GENERAL (MECHANICAL) ROOM VENTILATION IS EXPECTED TO BE SATISFACTORY.

Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: CHEM WORK GOG/FULL LGTH FACESHLD (FP N).

Other Protective Equipment: NONE.

Work Hygienic Practices: THOROUGHLY CLEANSE HANDS AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health: PH: 8.0-9.0.
=====

Physical/Chemical Properties
=====

B.P. Text: 212F,100C

Decomp Text: 240F,116C

Vapor Pres: ING 1

Vapor Density: LTR/AIR

Spec Gravity: 1.23

PH: SUPDAT

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: APPRECIABLE

Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume: 50
=====

Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: NONE KNOWN.

Materials To Avoid: MATERIALS INCOMPATIBLE WITH WATER.

Hazardous Decomposition Products: THERMAL DECOMPOSITION WILL YIELD CARBON MONOXIDE, CARBON DIOXIDE, AND FRAGMENTED SHORT-CHAIN HYDROCARBONS.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT.
=====

Toxicological Information
=====

Ecological Information
=====

=====
=====
MSDS Transport Information
=====
=====

=====
=====
Regulatory Information
=====
=====

=====
=====
Other Information
=====
=====

=====
=====
HAZCOM Label
=====
=====

Product ID: VINYL MASTIC WEATHER BARRIER, WC-7

Cage: 14947

Company Name: VIMASCO CORP

PO Box: 516

City: NITRO WV

Zipcode: 25143 US

Health Emergency Phone: 304-755-3328

Date Of Label Review: 12/16/1992

Label Date: 12/16/1992

Chronic Hazard IND: N

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: COMBUSTIBLE. KEEP AWAY FROM HEAT AND OPEN FLAME.

ACUTE: MAY CAUSE MILD IRRITATION TO EYES, SKIN AND NASAL PASSAGES.

CHRONIC: NONE SPECIFIED BY MANUFACTURER.

=====
=====
Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not

a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.